


- NOTES:
1. DISPLAY TYPE: TFT
 2. OPERATING TEMP: $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
 3. STORAGE TEMP: $-30^{\circ}\text{C} \sim 80^{\circ}\text{C}$
 4. LCD DRIVER: COG (IC: LI19486L) ;
 5. BACKLIGHT: 8 CHIP-WHITE LED
 6. GENERAL TOLERANCE: ± 0.20
 7. ROHS



REV	DESCRIPTION	DATE
0-1	ISSUE	14.11.21

DRAWN BY:	ME CHECKED BY:	EE CHECKED BY:	APPROVED BY:
SCALE: 1:1	SHEET NO: 1 OF 1	UNIT: mm	

PN	SYMBOL
1	X(L)
2	Y(O)
3	X(R)
4	Y(O)
5	OND
6	DDVCC (1.8V/2.8V)
7	VCI (2.8V)
8	PA/RK
9	CS/SPI CS
10	RS/A0 (4#)
11	WR/SPI SCL/SGK
12	RD
13	SP1 SDI/SDA
14	SP1 SDO
15	RESSET
16	ND
17	DB0
18	DB1
19	DB2
20	DB3
21	DB4
22	DB5
23	DB6
24	DB7
25	DB8
26	DB9
27	DB10
28	DB11
29	DB12
30	DB13
31	DB14
32	DB15
33	A
34	K
35	K
36	K
37	OND
38	IM0
39	IM1
40	IM2